

MITEL NETWORKS

5201 | IP Phone

Cost-effective, Single-line IP Phone



The Mitel Networks™ 5201 IP Phone is a basic entry-level IP phone for easy access to telephony and messaging services. It is ideal for users or locations requiring access to basic call handling and network features.

For Occasional Users and Common Areas

The 5201 IP Phone is specifically designed for occasional and non-communications intensive users. It is also an affordable choice for common areas such as reception and meeting areas, manufacturing and retail floors, as well as offices of non-communications-intensive users.

Industry's Widest Range of IP Phones

The 5201 IP Phone is one in a series of IP phones designed to meet the diverse communication needs of users across the enterprise – from affordable entry-level IP phones to sophisticated network appliances. All are designed with ergonomics and modern office esthetics in mind.

Features*

- Four function keys: Hold, Message, Transfer/Conference or Redial, Volume
- Call hold
- Call transfer
- Conference calls
- Voice mail access – large message waiting lamp
- Ringer volume control
- Wall mountable



it's about **YOU**

Voice QoS

Supports 802.1p/q for quality of service.

Powering Options

Available with AC adapter; accepts standards-based (IEEE 802.3 af) power over the LAN via spare or signal pair.

Environmental Conditions

	Temperature	Humidity
Operational	+4°C - +40°C	34%
Storage	-25°C - +66°C	15%

Regulatory Standards

EMC	CLASS B (FCC-Part 15)
Network	FCC-Part 68 (US), CS-03 (Canada)

System Requirements

- Mitel Networks 3100 Integrated Communications Platform, release 4.0
- Mitel Networks 3300 Integrated Communications Platform, release 3.3
- Mitel Networks SX-200 IP Node Lightware 19, release 3.1

5201 IP Phone Specifications

Ports	AC Adapter	Consumption	Processor Type	Processor Speed	Silicon	Package
1	Output: 48 Vdc 250 mA Input: 110 V 50-60 Hz 220 V 50 Hz	1.7 W	ARM7TDMI	25 MHz	0.18µ CMOS	QFP
Voice Traffic	Signaling	Ethernet	Size (LxW)	Weight	MTBF Rate	Compression
RTP over UDP	MiNET over TCP	IEEE 802.1p/q	6.5" x 6" 16.5 cm x 15.25 cm	1.7 lbs 0.77 kg	10 yrs	G.711

*Not all features are supported across all IP platforms. Refer to the Mitel Networks 3100 Integrated Communications Platform (ICP) data sheet, the Mitel Networks 3300 Integrated Communications Platform (ICP) brochure, and the SX-200 IP Node data sheet for more detailed information.

North America (613) 592 2122 1 800 648 3579	Europe, Middle-East & Africa Sales: 0870 9093030 Int: +44 (0) 1291 430 000	Latin America (613) 592 2122 1 800 648 3579	Asia-Pacific Tel: +852 2508 9780 Fax: +852 2508 9232
----------------------------------------------------------	---------------------------------------------------------------------------------------------	----------------------------------------------------------	-------------------------------------------------------------------

www.mitel.com



THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel Networks to be accurate as of the date of its publication, is subject to change without notice. Mitel Networks assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2003, Mitel Networks Corporation. All Rights Reserved.

GD 6336 PN 51005780, Rev. B