

M3904 PROFESSIONAL TELEPHONE

TECHNICAL SPECIFICATIONS

Dimensions

Width: 11.25 in. (286 mm)
Depth 1: 7.75 in. (197 mm)
Depth 2: 6.75 in. (171 mm)
Height 1: 5.13 in. (130 mm)
Height 2: 7.00 in. (178 mm)
Weight: 2.38 lb (1.08 kg)

Note: Depth 1 and Height 1 measured with the phone in the lowest position on the footstand. Depth 2 and Height 2 measured with the phone in the highest position on the footstand.

Color

- Charcoal or Ash

Operating Environment

Temperature

- 0° C to 50° C (32° F to 122° F)

Relative Humidity

- 5% to 95%

Auxiliary Power (M3902 and M3903 only)

- Local Plug-in AC Transformer for cartridge-style accessories

Loop Length

- 4,000 ft (1,220 m) 24 AWG

Standards

- Meets or exceeds applicable CSA, UL, and EIA specifications. Complies with FCC requirements for hearing-aid compatibility. Maximum handset volume control levels are compliant with the Americans with Disabilities Act (ADA).

Prerequisites

Meridian 1

- X11 Software Release 24.2x and higher
- Intelligent Peripheral Equipment (IPE) based Digital Line Card

Meridian SL-100

- MSL11 software and higher
- M3900 Release 2 firmware and higher
- Intelligent Peripheral Equipment (IPE) based Digital Line Card with Enhanced XPEC card